

ZEITH APACHI Ultimate ESP 5W-40 SN series

Extend. Save. Protect.
Advanced Technology Fully Synthetic Engine Oil



Product Data Sheet

Product Description

ZEITH APACHI Ultimate 5W-40 ESP SN series is an advanced technology fully synthetic high performance engine oils blended in severely refined fully synthetic basestocks fortified with sophisticated additive technology, specifically to provide extended oil drain intervals, save fuel consumption, protect antipollution systems and improve overall engine performance. It helps prolong the life and maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobile engines, with recent multivalve engines equipped with turbochargers and direct injection fuel systems. Low content in Sulphated Ash, Phosphorus and Sulphur reduces particulate build up in Diesel Particulate Filters (DPF's) and avoids poisoning of Gasoline Catalytic Converters (CAT's)

Features & Benefits

- Extended oil drain intervals (>20,000 km), due to fully synthetic nature of baseoils and advanced additive technology.
- Reduced oil consumption, due to stringent low volatility requirements of ACEA C3/C2-12 & other OEMs.
- Excellent fuel economy & easy cold starts due to extreme fluidity at low temperatures.
- Optimization of the anti-pollution systems and enhancing its life & efficiency, especially in DPFs & CATs.
- Improved additive technology, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, keeps oil in grade, lower acid formation & extend drain intervals.
- Outstanding engine protection, helps maintain longer engine life and compatibility with engine seals.

Specifications

ZEITH APACHI Ultimate ESP 5W-40 SN meets or exceeds following International and Builder

- API SN, CF
- ACEA C3/C2-16
- BMW Longlife-04
- VW 502/505.00/505.01
- MB 229.31/51/52
- GM dexos2, Hyundai, Kia

ZEITH APACHI Ultimate ESP 5W-40 SN meets or exceeds following International and Builder

- API SN, CF
- MB 229.31/51
- ACEA C3-16
- GM dexos2, Hyundai, Kia

OEM Approval: ZEITH APACHI ULTIMATE ESP 5W30 SN holds MB-Approval 229.52

Application

ZEITH APACHI Ultimate ESP 5W30 SN is suitable for use in following:

- Both Gasoline and Diesel Passenger cars, SUVs, light trucks and vans, equipped with DPF, SCR, CAT, SOC.
- Suitable for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines
- Suitable for Euro IV standards in most severe conditions of use like latest downsized engines with latest technology of stop & start functionality for fuel savings, sports driving, city and motorway driving.

Typical Characteristics

Zeith Apache Supreme	Test Method	Units	5W-20	5W-30	5W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.845	0.845	0.850
Viscosity @ 100 °C	ASTM D 445	cSt	8.2	10.4	14.30
Viscosity @ 40 °C	ASTM D 445	cSt	43.05	58.65	88.6
Viscosity Index	ASTM D 2270	-	169	169	168
Pour Point	ASTM D 97	°C	-39	-39	-39
Flash Point (COC)	ASTM D 92	°C	215	225	225
Total Base Number	ASTM D 2896	mg KOH/g	7.2	7.2	7.2
Phosphorous	ASTM D 4951	% wt	0.077	0.077	0.077
CCS Viscosity	ASTM D 5293	cP	5250 @ -30 °C	5600 @ -30 °C	5600 @ -30 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.